

Add:Ruian City ,Wenzhou City, Zhejiang Province ,China

HWFPS-4800 SEPARATE 4 COLOR FLEXO PRINTING MACHINE



CONTROL PART

- 1. Main motor frequency control, power
- 2. PLC touch screen control the whole machine
- 3. Reduce motor separate

UNWINDING PART

- 4. Single work station
- 5. Hydraulic clamp,hydraulic lift the material , hydraulic control the unwinding material width , it can adjust left and right movement.
- 6. Magnetic powder brake auto tension control
- 7. Auto web guide

PRINTING PART

- 1. Pneumatic lifting and lowing printing plate cylinders auto lifting plate cylinder when the machine is stopped. After that can run ink automatically. When the machine is opening, it will make alarm to start the auto lowering plate printing cylinder.
- 2. Inking with ceramic anilox chambered doctor blade ,ink pump circulation
- 3. High precision planetary gear oven 360°circulation longitudinal register
- 4. ±20mm transverse register
- 5. Adjust inking press and printing pressure press by

manual

DRYING PART

Adopt with external heating pipe, temperature display, electric current control,centrifugal blower bring the wind

REWINDING PART

- 1. Back to back rewinding
- 2. Pneumatic tension control
- 3. 2.2kw motor , vector frequency conversion control
- 4. 3 inch air shaft
- **5.** Hydraulic lowering the material

COMPOSITION

	Name	Origin
1	Main motor	CHINA
2	Inverter	Inovance
3	Rewinding motor	CHINA
4	Rewinding Inverter	CHINA
6	Inking reducer	CHINA
7	All of the low voltage control switch	Schneider
8	Main bearing	TAIWAN
9	Roller bearing	CHINA
10	PLC Touch Screen	OMOROM

STRUCTURE

1. The machine adopt with synchronous belt drive and hard gear face gear box. The gear box adopt with synchronous belt drive each printing group high precision planetary gear oven(360° adjust the plate) gear driving the press

printing roller

2. After printing, long running material space ,it can make the ink drying easily,better results

PARAMETERS


ТҮРЕ	HWFPS-4800
Max. Printing material width	800mm
Max. Printing width	760mm
Printing length range	230-800mm
Printing speed	5-100m/min
Register precision	≤±0.20mm
Thickness of plate (including the thickness of double sides glue)	2.28+0.38

Printing Unit

Chamber Doctor Blades & Ceramic Roller



Single Doctor Blade & Ceramic Roller



Helical Gears



Printing Sample



